

# AVK SURFACE BOX H-4055VF HD-GG

#### Height adjustable with Fugenring Surface box for underground hydrants Standard lid inscription: HYDRANT

Type

- H-4055VF HD-GG
- -Oval cast iron lid
- -Oval top surface box

### Features

- Lightweight, user-friendly, silent and maintenance free
- 100% recyclable and significantly less use of resources compared to traditional materials
- Manufactured out of high grade recycled materials
- Ribs in housing ensure optimal fixation in road foundation
- Selected materials for housing and lid ensure easy opening at all times
- Heat resistant to max. 250 °C
- Suitable for low-temperature applications
- Large height range and flexible positioning of top part
- · No height adjustment needed after installation, saving time and costs
- Floating top part following road settlement ensuring perfect alignment at all times
- Reinforced rim ensures better support of top part
- Durable joint between tarmac and surface box
- Installation according to ZTV Fug-StB 15 guidelines
- D400 load bearing capacity

#### Optional

- · Spring around bolt ensuring lid will stay in its place
- Various colours and lid inscriptions possible
- Available as lockable version making the surface box tamperproof
- Use of a Flexdrain around the hydrant prevents dirt to block the drain pipe, ensuring optimal operation

#### Standards

- Design according to DIN 4055
- DVGW VP 310-2
- DVGW approval, certificate DW-4530BN0469

#### Accessories


Support tile III










## AVK SURFACE BOX H-4055VF HD-GG









## **Component list**

PA
EN-GJL-200
A2-70
PA+
PA+

## Reference nos. and nominal dimensions

AVK ref. nos.	D1 mm	D2 mm	D3 mm	D4 mm	D5 mm	D6 mm	D7 mm	D8 mm	D9 mm	D10 mm
80-30-3900000	397	275	325	380	444	292	210	47	220	277
	D11 mm	D12 mm	D13 mm	H mm	X mm	Weight box in kg	Weight lid in kg	Total weight in kg		
	342	342	237	420-555	80-215	8.1	10.8	18.9		
For other variants different item Dimensions are subject to tolera										

The designs, materials and specifications shown are subject to change without notice due to the continuous development of our product programme.